


4.2 Two-dimensional arrays

- The following figure illustrates a two-dimensional array, a, containing three rows and four columns.



© Dr Izeddin Hidar 2007

- To allocate two-dimensional array named “a” which have 10 rows and 5 columns of type int :


```
int [,] a = new int [10,5];
```

 Or


```
int [,] a ;
a= new int [10,5];
```
- The a array contains 50 (10 x 5) elements.
- We can initialize the two-dimensional array elements using { and } delimiters in the same way as in the single dimensional array.


```
double [,] B =new double [2,4]{{ 4,8,6,2},{ 5,1,8,4 }};
```


 or


```
double [,] B ={{ 4,8,6,2},{ 5,1,8,4 }};
```
- For example:

Write a program to input the array A to the computer memory, calculate its Max value and display this array and its max value.

$$A = \begin{bmatrix} 2 & 4 & 6 \\ 1 & 2 & 3 \end{bmatrix}$$

© Dr Izeddin Hidar 2007



© Dr Izeddin Hidar 2007

```
private void ButCalculate_Click(object sender, EventArgs e)
{
    int[,] A = { { 2, 4, 6 }, { 1, 2, 3 } };
    int Max = A[0, 0];
    string s = "Your array is:\n";
    for (int i = 0; i < 2; i++)
    {
        for (int j = 0; j < 3; j++)
        {
            if (A[i, j] > Max) Max = A[i, j];
            s += A[i, j].ToString() + " ";
        }
        s += "\n";
    }
    s += "\nMax=" + Max.ToString();
    MessageBox.Show(s);
}
```

© Dr Izeddin Hidar 2007